

Loudspeakers

Cuboid 8

Two-way, full range, passive, 8" loudspeaker



Optimal Audio



FEATURES

- Compact sized wooden cabinet
- Portrait or landscape mounting options
- Rotatable high-frequency horn
- 90Hz - 20kHz frequency response
- Max SPL 115dB (cont), 121dB (peak)
- 90° horizontal x 50° vertical coverage

Cuboid 8 is a full range, two-way, passive, 8" loudspeaker designed to outperform its compact size. For short to medium throw distances, it effortlessly delivers rich and detailed sound with punch and precision.

With its wooden cabinet, steel grille and optional mounting hardware the professionally presented Cuboid 8 can be fixed in either portrait or landscape mode for a flexible, simple installation.

Cuboid 8 features an 8" (200mm) low frequency (LF) driver for impressive punch and midband with a 1" (25mm) exit high frequency (HF) compression driver for clarity of vocal and high frequency projection. The HF section delivers consistent coverage in either plane from a user-rotatable horn.

When coupled with the Zone series, a ZonePad and the WebApp makes setting up a system and end user control simple and intuitive.

APPLICATIONS



Cafes



Bars/
Restaurants



Retail



Wedding
Venues



Hotels



Education
Facilities



Houses of
Worship



Corporate
Offices



Museums



Fitness Studios



Residential










Loudspeakers

Cuboid 8

Two-way, full range, passive, 8" loudspeaker



Optimal Audio



SPECIFICATIONS

TYPE	Two-way, full range, passive loudspeaker
FREQUENCY RESPONSE (with preset)	90Hz - 18kHz \pm 3dB -10dB @ 62Hz
DRIVERS	LF: 8" (200mm), ferrite motor system HF: 1" (25mm) exit/1" (25mm) voice coil, HT polymer dome compression driver
RATED POWER	200W (AES) 800W (peak)
NOMINAL IMPEDANCE	8 Ω
SENSITIVITY (1W/1m)	92dB
MAXIMUM SPL	115dB (cont), 121dB (peak)
RECOMMENDED AMP	SmartAmp 30
CROSSOVER	2.9kHz passive
DISPERSION (-6dB)	90° H x 50° V (user-rotatable)
ENCLOSURE	Trapezoid wooden cabinet
FINISH	Black textured paint / White finish by special order
PROTECTIVE GRILLE	Black perforated steel with scrim cloth backing
CONNECTORS	1x NL4, 1x 4 pin Euroblock
PIN CONNECTIONS	NL4 Input only 1+/1-, 4-pin Euroblock with +/- for input and +/- for link connections
FITTINGS	16 x M8, inset bolts
DIMENSIONS	(W) 256mm x (H) 422.5mm x (D) 261mm (W) 10.08" x (H) 16.63" x (D) 10.28"
WEIGHT	10kg (22.05lbs)
ACCESSORIES (available separately)	Wall Bracket A, U Bracket A, M8 Eye Bolt
RECOMMENDED SUB	Sub 10 or Sub 15



Black

Textured
Paint Finish



White

Special
Order



10.0
kg

22.05
lbs

Weight

optimal-audio.co.uk

© 2026. Optimal Audio Group Ltd.